



Fuller® 13-Speed Transmissions

RTLO-12913A

RTLO-16913A

RTLO-20913A

RTLO-14913A

RTLO-18913A


Roadranger®

More time on the road™

The Low-Inertia™ Super 13

Versatility and low shift effort in a premium Fuller® transmission.

- “Super 13” features patented low-inertia design concept that makes shifting smoother, faster, and easier than ever before.
- Ratio flexibility with 16.9 to 1 overall reduction.
- Gathered gear ratios in hi-range provide potential fuel savings by helping keep RPM's low to remain in the engine's optimum fuel efficiency band.
- Simplified shifting with preselect on all button shifts.
- Faster, smoother range and splitter shifts and improved cold weather performance due to design improvements.
- On selected models an optimized lubrication system provides increased cooling and lubrication for more difficult, harder working applications.
- Quieter operation and increased durability with helical gears in auxiliary section.
- 0.73 and 0.86 overdrives for optimum cruise RPMs.
- Roadranger warranties are available for a wide variety of applications. To find the coverage that applies to your specific vocation, please see the Vocational Warranty Guide, at www.roadranger.com.



Fuller® 13-Speed Transmissions

SPECIFICATIONS	CAPACITY	WEIGHT*	LENGTH**	SPEEDS
RTLO-12913A	1250 lbs.ft. [1695 Nm]	714 lbs. [324 kg]	33.1 in. [841 mm]	13 forward, 3 reverse
RTLO-14913A	1450 lbs.ft. [1967 Nm]	714 lbs. [324 kg]	33.1 in. [841 mm]	13 forward, 3 reverse
RTLO-16913A	1650 lbs.ft. [2237 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 3 reverse
RTLO-18913A	1850 lbs.ft. [2508 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 3 reverse
RTLO-20913A	2050 lbs.ft. [2779 Nm]	716 lbs. [325 kg]	33.1 in. [841 mm]	13 forward, 3 reverse

* Less clutch housing, lubricant and end yoke.

** Lengths listed are from face of clutch housing to front bottoming surface of companion flange or yoke.

Clutch Housing:

SAE # 1 and # 2. Cast iron and aluminum available.

PTO Openings:

Right side, a 45-tooth 6/8 pitch gear. Left side, a 47-tooth 6/8 pitch gear. Both gears turn at .79 of engine speed.

Oil Capacity:

Approx. 28 pints [13.25 liters]. Integral oil pump available. Standard on 16913A and 18913A. Oil to water heat exchanger standard on 18913A and 20913A models (Requires 2 pints [.95 liters] additional lubricant. Adds 10 lbs. [4.55 kg] to weight).


Low Inertia Concept:

This innovative, patented design is identified in the Eaton Fuller nomenclature by the letter "L" (as in RTLO-14913A).

These transmissions feature a simple mainshaft which is not splined to the auxiliary gear. This unique design eliminates the added mass, drag and inertia of the entire auxiliary section.

During upshifts, where both the lever and splitter button are moved together, the low-inertia mainshaft is quickly brought to synchronous resulting in fast, easy shifts.

Performance Chart: RTLO-18913A




Based on 1800 RPM engine operating at 1636 RPM/62 MPH [100 kph].

Ratios and Steps:

GEAR	RATIO	% STEP
8th H	0.73	17
8th L	0.86	17
7th H	1.00	17
7th L	1.17	18
6th H	1.38	17
6th L	1.62	19
5th H	1.94	17
5th L	2.28	41
Range Shift		
4th	3.23	37
3rd	4.43	38
2nd	6.11	40
1st	8.59	42
Low 1	12.31	
Reverse-HI	3.50	
Reverse-Low	13.22	
Overall Ratio:	16.9 to 1	

Shift Pattern:



Roadranger®



EATON

For spec'ing or service assistance, call 1-800-826-HELP (4357) 24 hours a day, 7 days a week (Mexico: 001-800-826-4357), for more time on the road. Or visit our web site at www.roadranger.com.

Roadranger: Eaton, Dana and other trusted partners providing the best products and services in the industry, ensuring more time on the road.